



EINAR

Traffic Monitoring Cameras

Smart Parking Made Simple

Einar is a fully automated plug-n-play camera with optional onboard ANPR and superior imaging. Its sleek design, super easy setup, and user-friendly interface make it ideal for any smart parking, slow traffic monitoring, and vehicle access projects.

Easy Installation and Operation

Preconfigured settings for direct ANPR and access control or slow traffic monitoring. IP-based remote access for convenient operation.

Powered with PoE+

Supplied by Power over Ethernet+ technology and GPIO connectivity, Einar allows for a simple single-cable connection.

User GPIO-port

Factory-supported GPIO-port for direct communication with universal controllers. This means no intermediary device is needed for opening and closing gates and barriers.

Powered by Carmen®

ANPR-ready Imaging or Onboard ANPR

Einar delivers ANPR-ready images, allowing you to integrate them into traffic monitoring systems. For convenient, on-the-spot license plate data processing, basic Einar models can be upgraded any time with onboard ANPR, powered by Adaptive Recognition's industry-leading Carmen® engine. Carmen® boasts outstanding confidence rates even with hard-to-read plates and global coverage: the trainable software is familiar with license plates used in 180+ countries worldwide. Wherever you are on the globe, Carmen® has you covered.

EINAR

Next Generation Smart Access Control

A Standalone Traffic Solution

The built-in software-based triggering guarantees that license plates are captured as soon as they appear on the screen. Paired with the onboard ANPR engine, you get results in the blink of an eye: images with ANPR data such as license plate, date & time, GPS location, and even video recordings. Results are directly exported to the chosen database. The GPIO-port allows Einar to send data and to communicate with universal controllers to open gates and barriers, and more.



Controllable Optics

Superior Imaging

Einar comes with a 5-megapixel color sensor unit with auto-adjustable optics, as well as built-in LED illumination. These features allow it to zoom and focus as needed, and tackle special light conditions and license plates with colored backgrounds.



EINAR



Ease of Use

Simple Installation and Interface

There is no need to configure the camera in any way - Einar captures vehicles all by itself and is easy to manage via IP-based remote access. All events are saved on an internal SD card accessible only for the operator.

Models

ANPR

| | Einar 5 (Standard) | Einar 5T (Telelens) | Einar 5W (White Illumination) |
|--|-----------------------|------------------------|----------------------------------|
| ANPR at 0 Lux | 1.5 m – 4 m | 4 m – 8 m | 1.5 m – 4 m |
| Maximum ANPR range at optimal conditions | 20 m | 35 m | 20 m |
| Maximum recommended vehicle speed | | 70 km/h* | |

Imaging

| | | | |
|--------------------------------------|----------------------|---------------|---------------|
| Resolution (HxV pixels) @ framerate | 2592 x 1944 @ 60 FPS | | |
| Lens & zoom (all auto and motorized) | 3 – 12 mm, 4x | 9 – 22 mm, 2x | 3 – 12 mm, 4x |
| Shutter | Rolling shutter | | |

Illumination

| | | |
|--------------------|-------------------|-------|
| Wavelength | 850 nm (infrared) | White |
| Illumination modes | Continuous | |

Processing & I/O

| | |
|-------------------------|---------------------------|
| CPU for ANPR | 1.25 GHz + HW accelerator |
| Communication protocols | NTP, TCP/IPv4, DHCP, DNS |

Electrical Data

| | |
|---------------------------|--------------------|
| Power requirement | PoE+ |
| Power consumption typical | 5 W |
| Connectivity | PoE+ (RJ45) & GPIO |
| SD-card slot | User accessible |

On-board Intelligence

| | |
|--|---|
| Carmen® ANPR | Optional |
| Video analytics | Vehicle detection, tracking, intelligent motion detection, alarms |
| Color + Make and Model Recognition (MMR) | - |
| Trigger sources | In-built video analytics |

Mechanical Data

| | |
|--------------------------------------|---|
| Internal operating temperature | 30°C – +85°C |
| IP rating | IP67 |
| Dimensions (without bracket) (LxWxH) | 167 x 126 x 100 mm |
| Weight (without bracket) | 1.2 kg |
| In the box | Camera, shield, bracket, IP67 RJ45 connectors (cables not included) |

Optional Accessories

Various brackets for different mounting solutions (i.e. hidden cables, pole mounting, wall mounting, ceiling mounting)

* Recommended maximum vehicle speed may be lower

Contact

ADAPTIVE RECOGNITION

www.adaptiverecognition.com



Check Product Details

Request information

Adaptive Recognition global offices



Adaptive Recognition **America**



Adaptive Recognition **Nordic**



Adaptive Recognition **Hungary**



Adaptive Recognition **Singapore**

Disclaimer

The information contained in this brochure is provided as is and without any warranties of any kind, whether expressed or implied, including but not limited to, implied warranties of satisfactory quality, fitness for a particular purpose and/or correctness. The contents of this brochure is for general information purposes only and do not constitute advice. Adaptive Recognition does not represent or warrant that the information and/or specifications contained in this brochure are accurate, complete or current and specifically stipulate that certain scanner details and specifications contained in this brochure may differ in available models. Therefore, Adaptive Recognition makes no warranties or representations regarding the use of the content, details, specifications or information contained in this brochure in terms of their correctness, accuracy, adequacy, usefulness, timeliness, reliability or otherwise, in each case to the fullest extent permitted by law.